

3

3

2

REVISIONS			
REV.	DESCRIPTION	DATE	
A	INITIAL RELEASE	03/07/07	
В	CHANGE DESCRIPTION OF ROLLERS FROM DRIVE SEAM TO DOUBLE SEAM	3/21/2007	

1

## **INSTALLATION INSTRUCTIONS:**

- 1. INSTALL ROLLERS, MARKED "T1" & "B1", ONTO THE SHAFTS AT THE LEFT SIDE, OR FEED SIDE OF MACHINE, PLACING "T1" ON THE UPPER SHAFT AND "B1" ON THE LOWER SHAFT.
- 2. REPEAT THE ABOVE PROCEDURE FOR THE REMAINING ROLLERS IN NUMERIC ORDER.
- 3. ALL ROLLERS MARKED "T" SHOULD BE ON THE TOP SHAFTS AND ROLLERS MARKED "B" SHOULD BE ON THE BOTTOM SHAFTS.
- 4. ALL ROLLER MARKINGS <u>MUST</u> FACE OUTWARD, OR TOWARDS THE OPERATOR.
- 5. MOUNT ENTRANCE GUIDE BAR (ITEM 15) ON THE STARTING SIDE OF THE MACHINE AT 1-1/8" OFF OF THE EDGE OF THE ROLLERS.
- 6. THE EXIT GUIDE BAR (ITEM 16) ON THE FINISHING SIDE SHOULD BE FLUSH AGAINST THE METAL AS IT EMERGES FROM THE ROLLERS.

## RAMS-2012 20 GA HYPERSPEED PITTSBURGH MACHINE



2

1

С

Е

D